This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.

THE BRITISH LIBRARY I REFERENCE AND INFORMATION SERVICE



ECTUAL PROPERTY ORGANIZATION International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT) WO 96/30314 (51) International Patent Classification 6: (11) International Publication Number: A1 3 October 1996 (03.10.96) C03C 13/06 (43) International Publication Date: (81) Designated States: AU, BR, CA, CN, CZ, FI, HU, IS, JP, KR, PCT/EP96/01181 (21) International Application Number: NO, NZ, PL, SI, SK, TR, US, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, TE, IT, LU, MC, NL, 19 March 1996 (19.03.96) (22) International Filing Date: PT. SE). (30) Priority Data: DE Published 31 March 1995 (31.03.95) 195 12 145.7 With international search report. (71) Applicant (for all designated States except TR US): ISOVER SAINT-GOBAIN [FR/FR]; Les Miroirs, 18, avenue d'Alsace, F-92400 Courbevoie (FR). (71) Applicant (for TR only): GRUNZWEIG + HARTMANN AG [DE/DE]; Burgermeister-Grunzweig-Strasse 1, D-67059 Ludwigshafen (DE). (72) Inventors; and (75) Inventors/Applicants (for US only): LOHE, Peter [DE/DE]; Ritterstrasse 5, D-67112 Mutterstadt (DE). HOLSTEIN. Wolfgang [DE/DE]; Herderstrasse 2, D-35315 Homberg (DE). SCHWAB, Wolfgang [DE/DE]; Beethovenstrasse 2, D-68723 Schwetzingen (DE). (74) Agent: KADOR & PARTNER; Corneliusstrasse 15, D-80469 Munich (DE).

(54) Title: A MINERAL FIBER COMPOSITION

(57) Abstract

A biodegradable mineral fiber composition, characterized by the following constituents in percent by weight: SiO₂ 45 to 60; Al₂O₃ 0 to 3; CaO 20 to 40; MgO 3 to 15; Na₂O 0 to 2; K₂O 1 to 10; Na₂O + K₂O 1 to 12; TiO₂ 0 to 3; Fe₂O₃ 0 to 3; others 0 to 5.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU -	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
		HU	Hungary	NO	Norway
BE	Belgium Burkina Faso	1E	Ireland	NZ	New Zealand
BF		ir	Italy	PL	Poland
BG	Bulgaria	.r	Japan	PT	Portugal
BJ	Benin	KE	Kenya	RO	Romania
BR	Brazil	KG	Kyrgystan	RU	Russian Federation
BY	Belarus	KP	Democratic People's Republic	STD	Sudan
CA	Canada	N.F	of Korea	SE	Sweden
CF	Central African Republic	. KR	Republic of Korea	SG	Singapore
CG	Congo		Kazakhstan	SI	Slovenia
CH	Switzerland	KZ		SK	Slovakia
CI	Côte d'Ivoire	u	Liechtenstein	SN	Senegal
CM	Cameroon	· LK	Sri Lanka	SZ	Swaziland
CN	China	LR	Liberia	7D	Chad
CS	Czechoslovakia	LT	Lithusnia		
CZ	Czech Republic	LU	Luxembourg	TG	Togo
DE	Germany	LV	Larvia	ŢJ	Tajikistan
DK	Denmark	MC	Monaco	TT	Trinidad and Tobago
EE	Estonia	MD	Republic of Moldova	UA	Ukraine
ES	Spain	MG	Madagascar	UG	Uganda
FI	Finland	ML	Mali	US	United States of America
FR	France	MN	Mongolia	UZ	Uzbekistan
GA.	Gabon	MR	Mauritania	VN	Viet Nam

WO 96/30314 PCT/EP96/01181

A mineral fiber composition

This invention relates to a mineral fiber composition which is biodegradable.

The prior art describes some mineral fiber compositions which are said to be biodegradable.

Biodegradability of mineral fiber compositions is of great importance since various studies indicate that mineral fibers with very small diameters in the range of less than 3 microns are suspected to be carcinogenic, while biodegradable mineral fibers with such dimensions show no carcinogenicity.

However, mineral fiber compositions must also have good workability by known methods for producing mineral wool with a small diameter, in particular the jet process. This involves in particular a sufficient processing range of for example 80°C and suitable viscosity of the glass melt.

The mechanical and thermal properties of mineral fibers, or the products made therefrom, are also of crucial importance. Mineral fibers are used for example for insulating purposes to a great extent. Sufficient temperature resistance of the mineral fibers is necessary in particular for use in the industrial sector.

The problem of the invention is to provide a novel mineral fiber composition which is distinguished by biodegradability, has good temperature resistance and can be processed well.

The invention is based on the finding that this problem can be solved by a mineral fiber composition which consists substantially of silicon dioxide and alkaline-earth oxides, and further contains substantially potassium oxide as a melting accelerator and a considerable proportion of aluminum ox-

ide for increasing temperature resistance.

It has turned out that such mineral fiber compositions fulfill the combination of necessary properties, namely biodegradability, sufficient temperature resistance for insulation objects in industry, as well as good workability in the production of the mineral wool as such and the products. This simultaneously means that the upper devitrification temperature of the melt is preferably under 1320°C. The mean fiber diameter is preferably 3 microns or less.

The inventive glass fiber compositions have considerable amounts of potassium oxide but only small amounts of sodium oxide. The presence of potassium oxide produces a clear increase in glass viscosity and improves temperature resistance by around 40 to 50°C as compared to sodium-containing glass.

The subject of the invention is a mineral fiber composition which is biodegradable, characterized by the following constituents in percent by weight:

SiO ₂	45 to 60
Al ₂ O ₃	0 to 3
CaO	20 to 40
MgO	3 to 15
Na ₂ O	0 to 2
κ ₂ 0	1 to 10
$Na_2O + K_2O$	1 to 12
TiO ₂	0 to 3
Fe ₂ O ₃	0 to 3
Others	0 to 5.

The inventive mineral fiber compositions are readily drawable in particular by the jet process, i.e. one obtains a

fine, low-shot mineral wool.

The mineral wool reaches a high temperature resistance of at least 740°C and shows good biodegradability.

The inventive mineral fiber compositions can preferably be melted in melting chambers fueled with fossile fuels, in particular natural gas, at melting temperatures from 1350 to 1450°C. Such melting chambers can produce a homogeneous melt, which is a prerequisite for constant product quality. Homogeneity of the glass melt also facilitates the reproducibility of the fiberizing process and thus of the thermal and mechanical product properties. Furthermore, the constant chemical composition of the thus produced mineral wool leads to controllable biodegradability.

In particular the addition of aluminum oxide increases the temperature resistance of the mineral wool.

The inventive mineral fiber compositions preferably have the following constituents in percent by weight:

siO ₂	.50 to 58
Al ₂ O ₃	0.2 to 2.5
CaO	25 to 35
мдО	5 to 10
Na ₂ O	< 1
к ₂ 0	2 to 8
$Na_2O + K_2O$	2 to 8
TiO ₂	0 to 1
Fe ₂ 0 ₃	0 to 1
Others	0 to 5.

Mineral fiber compositions are especially preferred with the following constituents in percent by weight:

SiO ₂	52 to 57
Al ₂ O ₃	< 2
CaO	28 to 34
MgO	6 to 9
Na ₂ O	< 1
K20	2 to 6
$Na_2O + K_2O$	2 to 6
TiO ₂	0 to 1
Fe ₂ O ₃	0 to 1
Others	0 to 5.

For assessment of biodegradability the standard powder test of the Deutsche Glasgesellschaft was used. This is an easily performed method and gives a sufficient measure of biodegradability. The method is described in L. Springer, "Laboratoriumsbuch für die Glasindustrie", 3rd ed. 1950, Halle/S, W. Knapp Verlag.

The thermal behavior of the mineral fibers was determined by the so-called "Swedish method". This method uses a silit pipe furnace with a horizontal working pipe open on both sides with a length of 350 mm and an inside diameter of 27 mm. In the center of the furnace there is a ceramic supporting plate with dimensions of 30 x 20 x 3 mm for positioning the test sample. The test sample has dimensions of 12 x 12 x 12 mm or 12 mm \emptyset x 12 mm height. The gross density is normally 100 kg/m³. The temperature increase is 5 K/min. The change in test sample height is determined continuously with a reading optic.

The invention will be described more closely in the following using examples.

Example 1

A mineral wool was produced with the following composition in percent by weight:

SiO ₂	55.6
Al ₂ O ₃	0.4
Fe ₂ O ₃	0.5
CaO	30.5
MgO	7.0
Na ₂ O	0.2
к ₂ 0	5.6.

This composition could be readily fiberized by the jet process at a drawing temperature between 1340 and 1400°C into mineral fibers with a mean diameter of 2.0 to 10 microns.

An investigation by the standard powder test of the Deutsche Glasgesellschaft yielded a value of 40 mg/kg and thus a value for high biodegradability.

Determination of thermal behavior by the "Swedish method" yielded a temperature resistance of 740°C with 5% height reduction.

Example 2

A mineral wool was produced with the following composition in percent by weight:

SiO ₂	53.4 ,	
Al ₂ 0 ₃	2.0	
Fe ₂ O ₃	0.3	
CaO	3.2 . 4	
Mg0	8.2	
Na ₂ O	0.4	
K ₂ O	2.6.	

This composition could be readily processed by the jet process at a drawing temperature between 1340 and 1400°C into mineral fibers with a mean diameter of 2.0 to 10 microns.

An investigation by the standard powder test of the Deutsche Glasgesellschaft yielded a value of 48 mg/kg and thus a value for high biodegradability.

Determination of thermal behavior by the "Swedish method" yielded a temperature resistance of 750°C with 5% height reduction.

-7-Claims

1. A mineral fiber composition which is biodegradable, characterized by the following constituents in percent by weight:

SiO ₂	45 to 60
Al ₂ O ₃	0 to 3 '
CaO	20 to 40
MgO	3 to 15
Na ₂ O	0 to 2
K ₂ O	1 to 10
Na ₂ O + K ₂ O	1 to 12
TiO ₂	0 to 3
Fe ₂ O ₃	0 to 3
Others	0 to 5.

2. The mineral fiber composition of claim 1, characterized by the following constituents in percent by weight:

SiO ₂	50 to 58
Al ₂ O ₃	0.2 to 2.5
CaO	25 to 35
MgO	5 to 10
Na ₂ O	< 1
K20	2 to 8
$Na_2O + K_2O$	2 to 8
TiOo	0 to 1

Fe₂O₃ 0 to 1
Others 0 to 5.

3. The mineral fiber composition of claim 1 or 2, characterized by the following constituents in percent by weight:

52 to 57 SiO₂ < 2 Al₂O₃ 28 to 34 CaO 6 to 9 Mg0 < 1 Na₂O 2 to 6 K20 2 to 6 $Na_{2}O + K_{2}O$ 0 to 1 TiO_2 0 to 1 Fe₂O₃ 0 to 1. Others

INTERN. JONAL SEARCH REPORT

International Application No PCT/EP 96/01181

A CT ASSIS	TICATION OF SUBJECT MATTER		·
IPC 6	C03C13/06		•
	International Patent Classification (IPC) or to both national classification	ation and IPC	
	SEARCHED		
Minimum do	cumentation searched (classification system followed by classification	symbols)	
IPC 6	C03C		
Documentate	on searched other than minimum documentation to the extent that su	th documents are included in the fields se	archea
			}
		seems terms used)	
Electronic da	ata base consulted during the international search (name of data base	and, where practical, seatth terms used,	
C. DOCUM	ENTS CONSIDERED TO BE RELEVANT	mani nastages	Relevant to claim No.
Category *	Citation of document, with indication, where appropriate, of the rele	evalit parage	
	DE 4 44 OT 250 (COMENTUETO & MADTI	MANN) 8	1-3
P,X	DE,A,44 27 368 (GRUENZWEIG & HART) February 1996	<i>u</i> 111111 <i>j</i>	Ì
	see the whole document		
•		ED) 30	1-3
X	FR.A.2 690 438 (SAINT GOBAIN ISOV	ER) 29	
	October 1993 see page 9		
			1 2
x	WO,A,92 09536 (PAROC OY AB) 11 Ju	ne 1992	1-3
	see the whole document		·
1	EP,A,O 459 897 (SAINT GOBAIN ISOV	ER) 4	
A	December 1991	•	
·		·	
ļ			
Fur	ther documents are listed in the continuation of box C.	X Patent family members are liste	i in annex.
* Special ci	ategories of cited documents:	T later document published after the ii or priority date and not in conflict	nternational filing date
'A' docum	nent defining the general state of the art which is not	ated to understand the principle of	theory underlying the
consta	dered to be of particular relevance r document but published on or after the international	"X" document of particular relevance; the	ne claimed invention
filing	date	cannot be considered novel of carri involve an inventive step when the	document is taken alone
l udnet	hent which may throw he publication date of another on or other special reason (as specified)	"Y" document of particular relevance; to	he claimed invention
O. docm	ment referring to an oral disclosure, use, exhibition or	document is combined with one or ments, such combination being ob-	Willie Office Specia cocca.
other	means ment published prior to the international filling date but	in the art. '&' document member of the same pat	
later	than the priority date claimed	Date of mailing of the international	
Date of the	e actual completion of the international search		
1 .	24 June 1996	- 1. 07. 96	
		Authorized officer	
Name and	a mailing address of the ISA European Patent Office, P.B. 5818 Patentiaan 2		
1	NL - 2280 HV Ripswik Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl.	LIBBERECHT, E	•
1	Fax: (+31-70) 340-3016	1	

INTERNA NAJ

NAL SEARCH REPORT

Int. Jonal Application No PCT/EP 96/01181

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE-A-4427368	08-02-96	AU-B- 2885895 CA-A- 2171447 WO-A- 9604213 FI-A- 961471 NO-A- 961335	04-03-96 15-02-96 15-02-96 01-04-96 01-04-96
FR-A-2690438	29-10-93	AU-B- 4263293 BR-A- 9305492 CA-A- 2110998 CN-A- 1078708 CZ-A- 9302865 EP-A- 0596088 WO-A- 9322251 HU-A- 67212 JP-T- 6508600 NO-A- 934725	29-11-93 11-10-94 11-11-93 24-11-93 19-10-94 11-05-94 11-11-93 28-03-95 29-09-94 20-12-93
 WO-A-9209536	11-06-92	SI-A- 9300218 SK-A- 146893 ZA-A- 9302874 FI-B- 93346	31-12-93 09-11-94 01-06-94 15-12-94 15-02-95
		AT-T- 117662 AU-B- 8908791 DE-D- 69107091 DE-T- 69107091 EP-A- 0558548	25-06-92 09-03-95 17-08-95 08-09-93
EP-A-0459897	04-12-91	FR-A- 2662688 AT-T- 121378 AU-B- 642493 AU-B- 7731891 CA-A- 2043699 CN-A- 1059135 DE-D- 69108981 DE-T- 69108981 ES-T- 2073136 HU-B- 212280 JP-A- 4228455 PL-B- 167825 US-A- 5250488	06-12-91 15-05-95 21-10-93 05-12-91 02-12-91 04-03-92 24-05-95 07-12-95 01-08-95 29-04-96 18-08-92 30-11-95 05-10-93